

United States Patent [19]

Yukitake et al.

[11] Patent Number:

5,745,182

[45] Date of Patent:

Apr. 28, 1998

[54] METHOD FOR DETERMINING MOTION COMPENSATION

[75] Inventors: Takeshi Yukitake; Shuji Inoue, both of

Yokohama, Japan

[73] Assignee: Matsushita Electric Industrial Co.,

Ltd., Osaka. Japan

[21] Appl. No.: 278,010

[22] Filed: Jul. 20, 1994

Related U.S. Application Data

[62] Division of Ser. No. 970,046, Nov. 2, 1992, Par. No. 5,369,449.

[30]	Fore	igu Ap	plicati	ion Priority Data	
Nov. 8.	1991	[JP]	Japan		3-293004

Jul. 9, 1992		Japan	4-131980
[51] Int C16	•		H04N 7/32

348/699, 400–402, 407, 409–412, 384, 390, 415; 382/232, 236, 238; H04N 7/137

[56] References Cited

U.S. PATENT DOCUMENTS

		Kaneko et al	
4,864.294			
4 000 000	1/1001	Chantelou et al	

(List continued on next page)

FOREIGN PATENT DOCUMENTS

0395271A2 10/1990 European Pat. Off. .

 0395440A2
 10/1990
 European Pat. Off.

 0447068A2
 9/1991
 European Pat. Off.

 0484140A2
 5/1992
 European Pat. Off.

OTHER PUBLICATIONS

A. Puri, et al, "Video Coding with Motion-Compensated Interpolation for CD-ROM Applications", Signal Processing. Image Communication, vol. 2, No. 2, pp. 127-144, Aug. 1990.

K. Kinuhata, et al. "Universal Digital TV Codec —Unicodec", 7th International Conference on Digital Satellite Communications. May 1986, pp. 281–288.

(List continued on next page.)

Primary Examiner—Richard Lee Attorney, Agent, or Firm—Watson Cole Stevens Davis, PL.L.C.

[57] ABSTRACT

A method for predicting motion compensation for determining of an input image based on a motion vector of the input image from this input image to a reference image which has been sampled at a first set time, and the method includes calculating a motion vector of the input image based on a move, at a second set time, of a block unit which is a part of the input image and consists of a plurality of pixels, and calculating a motion vector of the reference image based on a move, at the first set time, of a block unit which is a part of the reference image and consists of a plurality of pixels. Move compensation of the input image is calculated both from the motion vector of the input image and from the motion vector of the reference image, to thereby realize a method for determining motion compensation with high precision.

3 Claims, 6 Drawing Sheets

